



## A Series

- Meet various medium and high-end outdoor advertising scenarios needs
- Extremely Real Display Performance
- High Stability & Reliability
- Very Low Operating Cost Throughout Product's Life Cycle

### Specification

Model	A0421	A0621	A0821
LED type	SMD	SMD	SMD
Pixel pitch(mm)	4.44	6.66	8
Brightness(nit)	7500	7500-10000	7500-10000
Refresh rate(Hz)	≥3840	≥6000	≥15000
Grayscale(bit)	16	16	16
Power consumption (Max./Avg. ,W/m <sup>2</sup> )	570/190	660-680/220-227	675-700/225-233
Panel dimensions (WxHxD, mm/inch)	1280x960x70mm (50.39x37.8x2.76")	1280x960x72mm (50.39x37.8x2.83")	1280x960x72mm (50.39x37.8x2.83")
IP Rating	IP65 / IP54	IP65 / IP54	IP65 / IP54
Maintenance	Front/Rear	Front/Rear	Front/Rear
Certification	FCC, ETL, CE	FCC, ETL, CE	FCC, ETL, CE

Model	A1021	A1021D	A1621D
LED type	SMD	DIP	DIP
Pixel pitch(mm)	10	10.66	16
Brightness(nit)	7500-10000	10000	10000
Refresh rate(Hz)	≥15000	≥5000	≥26000
Grayscale(bit)	16	16	16
Power consumption (Max./Avg. ,W/m <sup>2</sup> )	675-700/225-233	260-330/87-110	270-330/90-110
Panel dimensions (WxHxD, mm/inch)	1280x960x72mm (50.39x37.8x2.83")	1280x960x80mm (50.39x37.8x3.14")	1280x960x80mm (50.39x37.8x3.14")
IP Rating	IP65 / IP54	IP65 / IP54	IP65 / IP54
Maintenance	Front/Rear	Front/Rear	Front/Rear
Certification	FCC, ETL, CE	FCC, ETL, CE	FCC, ETL, CE